

OXYMAX KIT

Portable Commercial Kit

The OxyMax Kit is the complete portable commercial HVACR kit for soldering, brazing, welding, cutting and heating on-the-go. The larger lightweight caddy features a rear pocket for extra storage, a torch holder to fit the included Precision, Pro and Power torch handles as well as an adaptor ring to allow brazing with either the 1L or 1.9L Ambro Oxygen cylinders (sold separately).

- DELIVERS MAXIMUM PORTABILITY FOR BRAZING IN COMMERCIAL HVACR
- COMPACT, PORTABLE, LIGHTWEIGHT & MULTI-FUNCTIONAL CADDY
- COMES WITH 3 TORCH SIZES: PRECISION, PRO AND POWER
- ENABLES BRAZING ON PIPES FROM 1/8" UP TO 3" IN SIZE
- SUITABLE FOR USE WITH 14.1 OZ (400G) MAP-PRO & 1L OR 1.9L OXYGEN CYLINDERS, SOLD SEPARATELY
- FITS 1L & LARGER 1.9L AMBRO OXYGEN CYLINDERS (ADAPTOR RING INCLUDED)



OXYMAX KIT



Portable Commercial Kit

Specifications

Item	OxyMax Kit
Product Number	1811170
Application	Commercial HVACR: Soldering, Brazing, Welding, Cutting, Heating
Barcode	9320688427212
Flame Adjustment	Yes
Fuel Type	Ambro Controls 1L and 1.9L Oxygen Disposable Cylinder and 14.1oz (400g) MAP-Pro Cylinder.
Torches Included	1 x Precision Torch with 6.5ft twin hose assembly w/ 4 tips, 0.037" (0.95 mm), 0.047" (1.2 mm), 0.053" (1.35 mm), 0.063" (1.6 mm). 1 x Pro Torch w/ 2 tips 0.0787 (2.0mm), 0.0945" (2.4mm) and a rosebud tip 0.0472" (1.2mm) 1 x Power Torch w/ 2 tips 0.028" (0.7mm), 0.035" (0.9mm) and a rosebud tip 0.0472" (1.2mm)
Hose Connection	Blue oxygen hose - (6.5ft length, 1/8" ID, CGA20) Orange gas hose - (6.5ft length, 1/8" ID, CGA21) * 6.5ft twin hose assembly included with Precision Torch
Regulator Connection	1 x Blue oxygen regulator - Inlet (M12x1) Outlet (CGA20) 1 x Orange gas regulator - Inlet (CGA600) Outlet (CGA21)
Flame temperature Air	up to ~5400°F (~3000°C)
Dimensions	17" H (42cm) x 12" W (31cm) x 8.25" D (21cm)
Net Weight	150 oz (4.25kg)
Weight	1L Oxygen: 169 oz (4.8kg) 1.9L Oxygen: 175oz (4.95kg) (11lbs) Based on assembled caddy with 1.9L Oxygen and MAP 14.1 oz (400g)
Included in Box	Precision torch w/ 6.5ft twin hose & 4 tips, Pro torch with 2 tips and Rosebud, Power torch w. 2 tips & rosebud, 2 check valves (torch end), oxygen regulator, fuel gas regulator, 6.5ft twin hose assembly, flint sparker, spanner, 3 spare o-rings, and caddy w/ oxygen cylinder adaptor ring.

